

Millepede Cable Rings™



Technical Specifications

The adjustable and reusable Millepede Cable Rings™ come in 4 sizes, (½ inch to 2 inches), as well as specialized versions for channel struts and distribution racks.

Size	Part Number	Adjustable to	Capacity (cat 5)
½ inch	MPCR-05-25-DT	½ inch to ¾ inch	1 to 12 cables
1 inch	MPCR-1-25-DT	¾ inch to 1 ¼ inch	12 to 35 cables
1 ½ inch	MPCR-105-25-DT	1 ¼ inch to 1 ¾ inch	35 to 68 cables
2 inch	MTMT-2-10-DT	1 ¾ inch to 2 ¼ inch	59 to 106 cables
2 inch Strut	MPSR-2-10-DT	N/A	60 to 64 cables
4 inch Strut	MPSR-4-10-DT	N/A	152 to 265 cables

Tensile Strength Millepede Cable Rings™

½ inch	55 inch lbs
1 inch	79.2 inch lbs
1 ½ inch	95.0 inch lbs
2 inch	114.0 inch lbs



Strength Millepede Strut Ready Cable Rings™

2 inch	228 pounds downward, 706 pounds side pull
4 inch	187 pounds downward, 626 pounds side pull

Material, Nylon 66 (polyhexamethylene adipamide)

UL 1565 Listed (Plenum) and UL 2043 Discrete Products, Air Handling Spaces

UV compatible per chemical manufacturer's product specifications.

Melting Point 255 degrees centigrade.

www.millepede.com

Millepede Europe & Middle East

Millepede Marketing Limited

P.O Box 5261
Milton Keynes, MK17 9RE
United Kingdom
Phone: +44 (0) 8708 030 910
Fax: +44 (0) 8708 030 920

Millepede Australasia

Millepede International Limited

Level 12, 251 Adelaide Terrace
Perth, WA 6000
Australia
Phone: +61 (8) 9221 3581
Fax: +61 (8) 9325 5313

Millepede Americas

Millepede Inc.

PO Box 732
Warren, PA 16365
United States of America
Phone: 1-716-355-4154
Fax: 1-716-355-4214